

# *P2010* *TBI*

IMPROVING PERFECTION





# IMPROVING PERFECTION

**P2010  
TBI**

IMPROVING PERFECTION

Fuel	Diesel/Jet A1 and SAF
Approval	CS-23   FAR23
Flight rules	VFR-VFR/N-IFR-PBN
Tailored for	PPL+HB+VFR/N-IR+PBN+SLPC
Direct operating costs	USD 180.40/h - € 141,82/h incl. TBR reserve

## TRUSTED BY FLIGHT SCHOOLS WORLDWIDE

AND MANY OTHERS

# P2010 TDI

IMPROVING PERFECTION

The **P2010 TDI** is where performance and comfort meet in one **complete IFR package**. **4 seats; 3 passenger doors; 1 baggage door.** Continental **CD-170**. Metal wings, landing gear and stabilator. Carbon fibre fuselage. Balanced controls. Unsurpassed stability.

**With the P2010 TDI your holidays will have a different taste.**

An aircraft that **burns just 6.3 US Gal per hour (less than 24 liters)** is no longer just a dream. It is no longer a dream to **cover almost 1,000nm or stay airborne for more than 14 hours** with the full-tank capacity of 63 US Gal (240 liters).

The TDI engine grants excellent **high-altitude performance with a fast cruise above 140 KTAS at 10,000ft** and a **service ceiling of 18,000 ft**.

**The P2010 TDI is the best way to reach your favorite destinations and live unforgettable moments.**



## Horsepower

170 hp




## Max Range

1.300 NM - 2.408 km



## Max Cruise

140 kts - 259 km/h



## Useful Load

893 lb - 405 kg



## POWERPLANT

The P2010 TDI is powered by the Continental CD-170, which is a liquid-cooled 4-cylinder in-line four-stroke Diesel engine with DOHC (double overhead camshaft). The valves are actuated by a cam follower. The operation of the direct Diesel injection engine is based on the common-rail technique and is turbo charged. The engine is controlled by a FADEC system that allows a management of power, with significant fully automatic mixture control (absence of related lever and always guarantees the best fuel/air ratio for every single cylinder). Engine monitoring is fully integrated inside the avionic suite screens.

## CABIN

Four seats, three passenger doors and one baggage door. This four-seater aeroplane boasts an expansive cabin featuring ergonomic front and rear seats with exceptional legroom and a separate third entry door. Alcantara leather and a dark ceiling improve your flying experience with unique elements. Your aircraft interior is made more exclusive with electrically adjustable comfort front seats, while guaranteeing absolute compliance with the industry's strictest standards.



## PERFORMANCE BASED NAVIGATION

The wide composite cabin allows for a large instrument panel with state-of-the-art avionics options: twin-screen G1000 Nxi IFR, new Flat-Panel Suite with integrated GFC700 autopilot. Performance-based Navigation (PBN), in simple terms, redefines the aircraft's required navigation capability from Sensor (equipment) Based to Performance-Based.



**P2010 MK3**  
UPGRADE

Enhance your P2010 experience with New Interior Design

**P2010  
TDI**

## TANGIBLE PROOF

Tecnam's choice of Jet-A1 fuel offers the following benefits:

- Reliability and safety thanks to the redundant **FADEC system (Full Authority Digital Engine Control)** without mechanical back-up;
- Significantly **lower operating costs due to lower consumption** and lower fuel prices for kerosene in many countries;
- **Comfortable operation;**
- **Jet fuel**, same as for civil and military jet aircraft;
- Compliance **with U.S. DoD requirements**: one single fuel;
- Consumption up to **50% (long-range cruise)** less fuel than comparable ignition engines;
- **Payload and range improvement;**
- **Instant start;**
- **Alternative choice** where AvGas is unavailable.

The P2010 TDI is ready to bring to your destination with Sustainable Aviation Fuels (SAF) which can save up to 80% net CO<sub>2</sub> emissions.



## Specs

### Continental CD-170 170 hp 3B Variable Pitch Propeller

PERFORMANCE		
Max Cruise Speed TAS	140 kts	259 km/h
Stall Speed (Flaps Down Power Off) CAS	53 kts	98 km/h
Service Ceiling	18.000 ft	5.486 m
Take-Off Run	1.457 ft	444 m
Take-Off Distance	2.306 ft	703 m
Rate of Climb	659 ft/min	3,34 m/sec
Landing Run	902 ft	275 m
Landing Distance	1.808 ft	551 m
Range (60% PWR - 10.000 ft)	1.300 NM	2.408 km

### DESIGN WEIGHT AND LOADING

Maximum Take Off Weight	2.690 lb	1.220 kg
Empty Weight, Standard	1.797 lb	815 kg
Useful Load	893 lb	405 kg
Baggage Allowance	88 lb	40 kg

### TYPICAL MISSION EXAMPLE

432 nm FL90 Mission [MTOW] 75% PWR	24,3 US gal - 92 lt	639 lb - 290 kg
610 nm FL90 Mission [MTOW] 75% PWR	34,4 US gal - 130 lt	573 lb - 260 kg

Mission #	% PWR	Fuel Consumption	Speed
1	75%	6,9 US gal/h - 26lt/h	119 ktas (6,000ft)
			122 ktas (9,000ft)
2	60%	6,3 US gal/h - 24lt/h	105 ktas (6,000ft)
			113 ktas (9,000ft)

## Standard Equipment

### Garmin G1000 Nxi

Includes:

- GDU 1050 10-inches PFD
- GDU 1054 10-inches MFD
- Dual GEA 71B Engine & Airframe unit
- Dual GIA 64WAAS Com/nav/GPS/GS/Loc
- GMA1360 Digital audio system
- GMU44B Magnetometer
- GDC72 Air data computer
- GRS79 AHRS
- GTP59 OAT
- GTX345R Mode S Transponder (ADS-B In and OUT)
- GFC 700 Autopilot Including Electronic Stability & Protection (ESP)

### Flight instruments and indicators

- Magnetic Compass
- GI 275/MD 302 Standby Attitude Module
- Pitot System Heated
- Static System
- Alternate Static Source
- Stall Warning Audible
- Stabilator Trim Position Indicator
- Rudder Trim Position Indicator

### Flight controls

- Hydraulic Toe Brakes
- Parking Brake
- Electrical Flaps
- Dual Flight Controls
- Castering Nose Wheel
- Aileron Lock and Elevator Lock
- Flight Trim Controls
  - Rudder with Indicator
  - Stabilator with Indicator
- Engine Controls:
  - Power
  - Alternate Air
  - Fuel Control Selector with LH/RH/OFF

### Electrical system

- Alternator, 28 Volt, 70 Amp
- Battery, 24 Volt 19 AH
- Rocker Switches:
  - Master Switch
  - Fuel Pump
  - Landing Light
  - Taxi Light
  - Navigation Lights
  - Strobe Light
- External Power Supply Receptacle
- Circuit Breaker Panel
- Static Discharge Wicks
- Landing/Taxi Light LEDI

### Fuel system

- Two Integral Fuel Tanks With 240 Litres (64 US gal) Total Capacity
- Engine Driven Fuel Pump
- Auxiliary Fuel Pump, Electric
- Fuel Tank Quick Drain
- Fuel Selector Valve, Left/Right/Off

### Exteriors lights

- Nav. Lights LED with Strobe Aveo Full LED TSO
- Landing/Taxi Light LED

### Interiors

- Pilot and Co-Pilot Seats Leather:
  - Adjustable Fore and Aft
  - Electric Vertical Adjustment
- Two Rear Passenger Seats Leather
- Seat Belts & Shoulder Harness, All Seats
- Wall To Wall Carpeting
- Hand Held Fire Extinguisher
- Map & Storage Pockets
- USB socket Type C
- Radio Call Plate
- Tow Bar
- Soundproofing
- Luggage Compartment
- Overhead Cockpit Speaker
- Four Position Intercom System
- First Aid Kit

### Exterior

- Epoxy Corrosion Proofing, All Structure
- LH/RH Front Door Pilot/Co-Pilot, Lock and Key
- Rh Rear Door Passenger
- Rh Baggage Door With Lock
- Rear Window
- All Lateral Windows Tinted
- Fixed Landing Gear
- White Polyurethane Exterior Paint
- Tie Down Rings
- Main Wheels, 6.00 X 6
- Nose Wheel, 5.00 X 5

### Cabin comfort system

- Windshield Defroster
- Ventilator adjustable, 4 Place
- Heating System
- Soundproofing
- Cabin Monoxide Detection System

### Powerplant and Propeller

- Continental CD170
- Tubular Steel Engine Mount
- Engine Driven Vacuum Pump
- Alternate Engine Air
- FADEC Power Lever
- Mixture Control
- MT - Constant speed propeller 3 blades
- Propeller Spinner
- Electric Starter

### Standard Avionics Package

also includes:

- Altitude Encoder
- Avionics Master Switch
- Mic & Phone Jacks / Lemo Plug Pilot/Copilot/Passengers
- Hand Held Microphone
- Avionics Circuit Breaker Panel
- Pilot And Co-Pilot PTT
- ELT 406

### Antennas

- Marker Beacon Antenna
- Transponder Antenna
- VHF Antenna
- NAV Antenna
- Emergency Locator Transmitter Antenna



“

*M*anufacturing an aircraft is not just a job, it is a challenge for perfection,  
driven by infinite passion and dedication

Paolo Pascale Langer | CEO

”

# P2010 TBI



Costruzioni Aeronautiche Tecnam SpA  
via Maiorise 81043 Capua (CE) - Italy

+39 0823 622297  
info@tecnam.com

Specifications, weights, representations, colors, list of equipment, use of materials and model references listed herein are not warranted or guaranteed to be true or accurate. Actual useful load will vary depending on options installed on the aircraft. Always consult specific aircraft weight and balance parameters and data for flight planning. The pictures contained in this brochure of specific models or other products may contain optional equipment or nonstandard features, which even if available may be at an additional cost. Some optional equipment may require separate paid subscriptions from third-party providers. You may rely only upon statements and representations contained in actual contracts that you enter into with TECNAM. Referenced TECNAM trademarks are owned by Costruzioni Aeronautiche TECNAM SpA or its subsidiaries. All other brands, product names, company names, trademarks and service marks are the properties of their respective owners. All rights reserved. ©2024, Costruzioni Aeronautiche TECNAM SpA.

[www.tecnam.com](http://www.tecnam.com)

